

SERIES LP LOW PROFILE

Capacities to 1600 lbs.

Standard Features

- Low overall height
- High capacities

Optional Features

1. Threaded Stems
2. Wheel Brakes
3. Conductive or anti-static wheels
4. Special finished or color matched powder coat
5. Swivel locks

APPLICATIONS:

Business machines, computers frames or furniture. Anything requiring high capacity and low overall height. Wide wheels and shortened swivel offsets give these casters the highest capacities in their size range.



SLP4A-RTR-3

3" wheel
Capacity to 500 lbs
Top plate: 3 1/8 x 4 1/8
Mounting: 2 3/8 x 3 7/16
Options: 2, 4



SLP1-HRP-2

2" dual wheel
Capacity to 270 lbs
Top plate: 2 9/16 x 3 5/8
Mounting: 1 3/4 x 2 7/8 - 3
Options: 1, 2, 3, 4



SLP2-XXX-XX

2" or 2 1/2" wheel
Capacity to 400 lbs
Top plate: 2 9/16 x 3 5/8
Mounting: 1 3/4 x 2 7/8 - 3
Options: 1, 2



SLP90-PBP-25

2 1/2" wheel
Capacity to 100 lbs
Top plate: 1 3/16 x 2
Mounting: 1 3/16 x 1 9/16
Options: 1, 2, 3, 4



SLP3-RTR-3

3" wheel
Capacity to 700 lbs
Top Plate: 3 1/8 x 4 1/8
Mounting: 2 3/8 x 3 3/8
Options: 1, 2, 4



SLP4X-XXX-3

3" wheel
capacity to 700 lbs
Top plate: 2 5/8 x 3 1/2
Mounting: 1 3/4 x 2 7/8 - 3
Options: 2, 3, 4



SLP2-PHR-26

2 5/8" wheel
Capacity: 240 lbs
Stem: 1/2 -13 x 3/4 or 1 1/2
Options: 2, 4



SLP14-RTR-3 & SLP14H RTR

3" wheel
Capacity to 1200 lbs
Top Plate: 3 5/16 x 4 5/16
Mounting: 2 3/8 x 3 3/8
Options: 1, 2, 4, 5




SLP14SA-RTR-3-XXXX

Shock Absorbing
3" wheel
Capacity to 1600 lbs
Top plate: 3 5/16 x 4 1/8
Mounting: 2 3/8 x 3 3/8
Options: 4, 5

Wheel Specifications					Caster Specifications						Part Number	
Dia. "A" Inches (mm)	Tread Inches (mm)	Wheel Composition & Brake Descriptions	Bearing Type	Axle Dia. Inches (mm)	Load Capacity lbs. (KGS)	Overall Height "B" Inches (mm)	Swivel Radius Inches (mm)	Finish	Attach. Bolt Inches (mm)	Approx. Shipping Wt. lbs. (KGS)	Swivel Caster	Rigid Caster
2 (50)	1 13/16 (21)	Hard Rubber - Dual Wheel	Self Lube	5/16 (8)	275 (124)	2 25/32 (71)	2 (50)	Zinc	5/16 (8)	1.25 (.56)	SLP1-HRP-2	RLP1-HRP-2
		Hard Rubber - Dual Wheel	Self Lube	5/16 (8)	275 (124)	2 25/32 (71)	2 (50)	Black	5/16 (8)	1.25 (.56)	SLP1-HRP-2-BL	RLP1-HRP-2BL
		Hard Rubber - Dual Wheel /Thumb Screw Brake	Self Lube	5/16 (8)	275 (124)	2 13/16 (71)	2 (50)	Black	1/2-13 x 1	1.25 (.56)	SLP1-HRP-2-BL-TB-41	-
	1 11/16	Polypropylene	Self Lube	5/16 (8)	300 (136)	2 27/32 (72)	2 (50)	Black	5/16 (8)	1 (.50)	SLP2-PBP-2-BL	-
2 1/2 (64)	1 13/16 (21)	Polyolefin / Side Brake	Self Lube	1/4 (6)	100 (45)	3 5/32 (80)	2 3/32 (53)	Zinc	3/16 (5)	0.38 (.17)	SLP90-PBP-25-SB	-
		Polyolefin	Self Lube	1/4 (6)	100 (45)	3 5/32 (80)	2 3/32 (53)	Zinc	3/16 (5)	0.38 (.17)	SLP90-PBP-25	-
	1 3/4 (45)	Polyolefin	Roller	7/16 (11)	400 (180)	3 1/2 (89)	2 1/8 (54)	Black	3/16 (5)	1.25 (.56)	SLP2-PBP-25-BL	RLP2-PBP-25BL
2 5/8 (67)	1 1/2 (38)	Phenolic Resin	Roller	7/16 (11)	240 (114)	3 5/16 (84)	2 1/2 (64)	Zinc	1/2-13 x 3/4	1.4 (.63)	SLP2T-PHR-26-17	-
		Phenolic Resin	Roller	7/16 (11)	240 (114)	3 5/16 (84)	2 1/2 (64)	Zinc	1/2-13 x 1 1/2	1.4 (.63)	SLP2T-PHR-26-12	-
3 (76)	1 13/16	Reinforced Thermoplastic Resin	Roller	3/8 (10)	500 (225)	4 (100)	2 1/2 (64)	Zinc	5/16 (8)	2.1 (.95)	SLP4-RTR-3	RLP4-RTR-3
		Polyolefin/Face Contact Brake	Roller	3/8 (10)	500 (225)	4 (100)	2 3/8 (60)	Zinc	5/16 (8)	2.6 (1.18)	SLP4-POR-3-B	RLP4-POR-3
	1 1/4	Polyolefin	Self Lube	3/8 (10)	270 (122)	3 13/16 (97)	2 3/4 (70)	Zinc	5/16 (8)	1 (.45)	SLP4-PBP-3	RLP4-PBP-3
	1 13/16 (46)	Reinforced Thermoplastic Resin	Roller	3/8 (10)	700 (315)	3 31/32 (100)	2 5/16 (59)	Zinc	5/16 (8)	2.3 (1.04)	SLP4H-RTR-3	RLP4H-RTR-3
		Phenolic	Roller	3/8 (10)	500 (225)	3 7/8 (98)	2 1/4 (57)	Zinc	5/16 (8)	2.3 (1.04)	SLP4W-PHR-3	RLP4W-PHR-3
		Reinforced Thermoplastic Resin	Roller	3/8 (10)	500 (225)	3 31/32 (100)	2 5/16 (59)	Black	5/16 (8)	2.3 (1.04)	SLP4A-RTR-3	RLP4A-RTR-3
		Reinforced Thermoplastic Resin	Roller	7/16 (11)	1000 (315)	3 31/32 (100)	2 7/16 (62)	Zinc	5/16 (8)	2.5 (1.13)	SLP3H-RTR-3	RLP3-RTR-3
		Reinforced Thermoplastic Resin	Roller	1/2 (13)	1000 (500)	4 5/32 (108)	2 3/8 (60)	Black	5/16 (8)	3.3 (1.50)	SLP14-RTR-3	-
		Reinforced Thermoplastic Resin	Roller	1/2 (13)	1200 (545)	4 5/32 (108)	2 3/8 (60)	Black	5/16 (8)	3.3 (1.50)	SLP14H-RTR-3	-
		Reinforced Thermoplastic Resin	Roller	1/2 (13)	900 (409)	***	2 7/16 (62)	Black	5/16 (8)	4.8 (2.18)	SLP14SA-RTR-3-900	-
Reinforced Thermoplastic Resin		Roller	1/2 (13)	1250 (573)	***	2 7/16 (62)	Black	5/16 (8)	4.8 (2.18)	SLP14SA-RTR-3-1250	-	
Reinforced Thermoplastic Resin	Roller	1/2 (13)	1600 (727)	***	2 7/16 (62)	Black	5/16 (8)	4.8 (2.18)	SLP14SA-RTR-3-1600	-		

*** Overall Height varies from 4 21/32 to 4 5/16 depending upon load.



OPTIONS:

			
WHEEL BRAKE	SWIVEL LOCK	THUMB-SCREW BRAKE	RIGID CASTER